



AF18 WG

TECHNICAL DATA SHEET

Introduction

- **AF18 WG** flaps wheel on which a process is carried out with a mixture of resins that adhere the individual strips together.
- The process does not change the main characteristics of **AF18 WG** flap wheels and leaves the flexible properties that characterize them.

Material: AF brown (maroon)

Mineral Type: Aluminum Oxide

Diameter: 200mm

Inner hole: 76mm

Thickness: Customized

Advantages

Application


- They can work in both directions of rotation.
- They maintain the shape more than normal **AF18 WG** flaps wheel even on complex parts
- They have a longer life.
- They have greater cutting power.
- Wood sanding
- MDF sanding
- Buffing UV paint and water base primer and plaster/chalk
- Satin-finish of hard metals

Sanding dimensions & Available hardness




Diameter \varnothing mm	Inner hole \varnothing mm	NWN	Impregnation
200	76	H5	H5I
250	115	H8	H8I
250	127	H10	H10I
300	127	SD	SDI
300	150	MD	MDI
350	200	HD	HDI
400	250		


Hardness form




H2/XSD




H5/SD



H8/MD



H10/HD



H12/XD

Head Office:

Via Delle Groane, 27/E 20024 Garbagnate M. -Mi- Italy

E-mail: itas.it@itasabrasivi.com

Website: www.itasabrasivi.com

I.T.A.S. ABRASIVES CO., LTD.

Yunxin Avenue, Yungang Road, 414009, Yueyang, Hunan, China.

Tel. +86 0730 3072778 / +86 0730 3072998

E-mail: itas.cn@itasabrasivi.com